

Universal cleaner

Triflex UltraCleaner



Product information

Applications

Triflex UltraCleaner is used as a universal cleaning and degreasing agent for treating Triflex surfaces.

Properties

Triflex UltraCleaner is a high-performance, water-soluble and reliable cleaner. The cleaner is biodegradable and alkaline in order to guarantee quick and efficient removal of dirt.

The types of soiling which can be removed include: Grease, dirt, carbon, oil, soot, nicotine deposits and other stubborn stains.

Pack size

Spray bottle

0.50 l Triflex UltraCleaner

Canister

10.00 l Triflex UltraCleaner

Storage

Can be stored unopened for approx. 12 months in a cool, dry place above 0°C. Avoid exposing the container to direct sunlight, even at the construction site.

Processing instructions

Spray bottle:

Apply Triflex UltraCleaner to the soiled surface with the spray bottle and allow it to take effect for a short time. Then use a cleaning brush to work at the soiling with circular movements, and rinse off with water. Finally wipe off the surface with a damp cloth.

Canister:

Normal soiling: 1 liter of Triflex UltraCleaner for 10 liters of water.

Heavy soiling: 1 liter of Triflex UltraCleaner for 5 liters of water.

Special applications: Triflex UltraCleaner can also be used undiluted. For example in the case of particularly heavy soiling such as rust or tire wear.

Important note:

Triflex UltraCleaner should not be used on glass or mirrors as there is a risk of discolouration.

Triflex UltraCleaner is not used to activate surfaces, and must not be used instead of Triflex Cleaner.



Notes on special hazards

See safety data sheet, section 2

Safety tips

See Safety Data Sheet, sections 7 and 8

Measures in case of fire or accidents

See Safety Data Sheet, sections 4, 5 and 6

General notes

We guarantee the consistently high quality of our products. Non-Triflex products must not be used with Triflex systems.

The advice we give in relation to the application of our products is based on extensive development and many years of experience, and is correct to the best of our knowledge. Given the multitude of on-site requirements, under the most varied of conditions, the user is required to test the product's suitability for its respective purpose. Technical information is subject to change without notice in the interests of technical advancement or enhancement of our products.