

Thickening agent

# Triflex Liquid Thixo



## Product information

### Applications

Triflex Liquid Thixo is used as a thickening agent in Triflex PMMA products to allow the coating of vertical surfaces. It is not suitable for EP or PUR products.

### Properties

Triflex Liquid Thixo is a thickening agent in liquid form.

### Pack size

Metal bottle

0.50 litre Triflex Liquid Thixo

### Colours

Transparent

### Storage

Can be stored unopened for max. 12 months in a cool, dry place above freezing at temperatures below +10 °C. Keep the container out of direct sunlight, even on the construction site.

### Mixing ratio

Amount to be added up to 1 % by weight

### Instructions for use

Triflex Liquid Thixo is evenly mixed into the PMMA base resin. After a maturing time of approx. 2 to 5 mins., thixotropy sets in. Triflex catalyst is then mixed in according to the product information for the PMMA product.



### Notes on special hazards

See Safety Data Sheet, section 2

### Safety tips

See Safety Data Sheet, sections 7 and 8

### Measures in case of fire or accidents

See Safety Data Sheet, sections 4, 5 and 6

### General notes

We guarantee the consistently high quality of our products. Non-Triflex products must not be used with Triflex systems.

The advice we give in relation to the application of our products is based on extensive development and many years of experience, and is correct to the best of our knowledge. Given the multitude of on-site requirements, under the most varied of conditions, the user is required to test the product's suitability for its respective purpose. Technical information is subject to change without notice in the interests of technical advancement or enhancement of our products.