

Primer

# Triflex ProDrain Primer



## Product information

### Applications

Triflex ProDrain Primer is used as a quick-filming and moisture-resistant primer on absorbent substrates such as concrete or screed in conjunction with the Triflex ProDrain system.

Triflex ProDrain Primer is used as a deep-penetrating primer and protects the Triflex ProDrain Fix+ adhesive from quick dehydration.

### Properties

2-component primer with a polymer dispersion base.

Triflex ProDrain offers the following quality features:

- Solvent-free
- Easy to use
- Prevents shrinkage cracks
- Improves adhesion

### Pack size

Plastic canister

5.00 kg Triflex ProDrain Primer

### Colours

White

### Storage

Can be stored unopened and unmixed for approx. 6 months in a cool, dry place above freezing. Keep container away from direct sunlight when in storage and on the construction site.

### Conditions for use

Triflex ProDrain Primer can be applied at substrate and ambient temperatures between +10°C and +35°C.

### Preparation of the substrate

Substrates must be sound, even, clean and free from adhesion-reducing residues. Make sure there is a sufficient gradient of at least 1%. Substrate adhesion must be tested on a case-by-case basis.  
Minimum tensile adhesion strength: 1.5 N/mm<sup>2</sup>

During application, the surface temperature must be at least 7°C above dew point. Below that, a separating film of moisture can form on the surface to be worked on (DIN 4108-5, table 1). See dew point temperature table.



### Mixing instructions

Triflex ProDrain Primer is diluted with water with a mixing ratio of 1:3.

It is not necessary to add a catalyst.

### Mixing ratio

1.00 l	Triflex ProDrain Primer
3.00 l	Water
4.00 l	

### Methods of application

Apply Triflex ProDrain Primer with a universal roller.

### Instructions for use

Apply Triflex ProDrain Primer evenly and generously with a universal roller. Mineral substrates can already be recoated after approx. 10 to 15 minutes. You can tell whether the Triflex ProDrain Primer has completely settled in from the white control colour. The control colour must still be visible, i.e. applied primer must still be visible as dark shading on the substrate when the Triflex ProDrain Fix+ adhesive is applied. If this is not the case, a new layer of Triflex ProDrain Primer will need to be applied.

### Material consumption

Approx. 0.15 l/m<sup>2</sup>

Primer

# Triflex ProDrain Primer



## Product information

### Notes on special hazards

See Safety Data Sheet, section 2

### Safety tips

See Safety Data Sheet, sections 7 and 8

### Measures in case of fire or accidents

See Safety Data Sheet, sections 4, 5 and 6

### General notes

We guarantee the consistently high quality of our products. Non-Triflex products must not be used with Triflex systems.

The advice we give in relation to the application of our products is based on extensive development and many years of experience, and is correct to the best of our knowledge. Given the multitude of on-site requirements, under the most varied of conditions, the user is required to test the product's suitability for the respective purpose. Technical information is subject to change without notice in the interests of technical advancement or enhancement of our products.