

Primer

# Triflex Bitumen Blocker



## Product information

### Applications

Triflex Bitumen Blocker is used as a primer for Triflex SmartTec / Triflex SmartTec Sp for all bituminous substrates, e.g. bare bitumen or bitumen welding seams.

### Properties

Single-component, unpigmented primer with an acrylate dispersion base. Triflex Bitumen Blocker offers the following quality features:

- Single-component
- Easy to use
- Solvent-free
- Odourless

### Pack sizes

Drum

10.00 kg Triflex Bitumen Blocker

### Colours

Whitish/transparent

### Storage

Store in a dry place at temperatures between +10 °C and +30 °C. Shelf life of 12 months if unopened. Keep container away from direct sunlight when in storage and on the construction site.

### Conditions for use

Triflex Bitumen Blocker can be applied at substrate and ambient temperatures from a minimum of +10 °C to a maximum of +30 °C.

### Preparation of the substrate

Substrates must be free of all loose, adhesion-reducing components. The substrate should have a minimum temperature of +10 °C and must not exceed +40 °C.

### Mixing instructions

The product can be applied immediately after opening the container.

### Coverage

At least 0,40 kg/m<sup>2</sup> on a smooth, even surface.



### Drying time

Approx. 3 hrs. at +20 °C

### Information on particular hazards

See Safety Data Sheet, section 2

### Safety advice

See Safety Data Sheet, sections 7 and 8

### Measures in case of fire or accidents

See safety data sheet, sections 4, 5 and 6

### General information

We guarantee the consistently high quality of our products. Non-Triflex products must not be used with Triflex systems.

The advice we give in relation to the application of our products is based on extensive development and many years of experience, and is correct to the best of our knowledge. Given the wide variety of on-site requirements and conditions, the user is required to test the product's suitability for the particular purpose. Technical information is subject to change without notice in the interests of technical advancement or enhancement of our products.