Nitrile rubber strip Triflex Support Strip

Product information

Applications

Triflex Support Strip is used as a support layer for the creation of a loop in settlement joints.

Properties

Triflex Support Strip is a polyester / polyamide fibre fleece with a 0.4 mm thick nitrile rubber strip. The fleece protrudes approximately 2.5 cm on both sides of the strip.


It is used to create an impregnation stop and to prevent adhesion of the waterproofing resin to the edges when applied in a joint.

Pack size

Roll

12.00 cm x 10 m	w x l	Triflex Support Strip 120
15.00 cm x 10 m	w x l	Triflex Support Strip 150
20.00 cm x 10 m	w x l	Triflex Support Strip 200

Top of Support Strip



Colours

Grey / White

Storage

Store Triflex Support Strip in a cool, dry enclosed space.



Application

Triflex Support Strip is used in conjunction with Triflex PMMA systems for the creation of loops in settlement joints. Bond the protruding fleece on the Triflex Support Strip to the edges of the joints with Triflex Cryl Paste, and lay the nitrile rubber strip in the joint as a loop. Then lay the Triflex Special Fleece, saturated with Triflex ProDetail, on the Triflex Support Strip as a loop in the joint and form the joint according to the relevant processing guidelines.

General notes

We guarantee the consistently high quality of our products. Non-Triflex products must not be used with Triflex systems.

The advice we give in relation to the application of our products is based on extensive development and many years of experience, and is correct to the best of our knowledge. Given the multitude of on-site requirements, under the most varied of conditions, the user is required to test the product's suitability for its respective purpose. Technical information is subject to change without notice in the interests of technical advancement or enhancement of our products.

